

REFERENCES

- Acierno, D., and Maio, L. D., The processability of waste thermo-plastics. An experimental approach with a simple two-component system, *J. Polym. Eng.*, **14**, 132 (1995).
- Block, D. G., Recycled resin prices weak, *Plastic Technology*, March ,**42** ,3 , 64 (1996).
- Bogardus, L. P., Effects of regrind of an extruded part, *SPE ANTEC Tech.*,**3** , 4288 - 2490 (1995).
- Cavaney, R., Plastic Bottle Recycling was up 21 % in 1994, *Plastic Engineering*, August , **51**, 8, 6 (1995).
- Dealy, J. M., Melt Rheology and its Plastics Processing, Van Nostrand Reinhold, 285 (1990).
- DiRaddo, R. W., Pecora, L., and Garcia-Rejon, A., Recycling of polyolefins in blow molding, *SPE ANTEC Tech.*, **1**, 1004 - 1005(1994).
- Dontula, N., and Compbell, G. A., A Study of Degradation of High Density Polyethylene in a Corotating Intermeshing Twin Screw Extruder, *Polym. Eng. Sci.*, **33**, 273, (1995).
- Doyon, J. F., Lafleur, P. G., Carreau, P. J., and Vergnes, B., Recycling of Polyolefins : processability and degradation, *SPE ANTEC Tech.*, **3**, 2876-2878 (1994).

Hinsken, H., Moss, S., Pauquet, J. R., and H. Zweifel, Degradation of Polyolefins during Melt Processing, *J. Polym. Degrad. Stab.*, **34**, 290 (1991).

Johnson , D., Plastics : The Environmental Challenge, Pims UK Ltd., London, 46-499 (1993)

Lavieri, N., Improving the melt flow properties of a recycled bottle grade HDPE, *SPE ANTEC Tech*, **3**, 2856 (1994).

Mark, H. F. , Encyclopedia of Polymer Science and Engineering, 2nd ed., John Wiley & Sons, New York, 458 (1986).

Mitterhofer, F., Processing Stability of Polyolefins, *Polym. Eng. Sci.*, **20**, 10, 694 (1980).

Niesen, L. E., Polymer Rheology, M. Dekker, New York, 81 (1977).

Pattanakul, C., Selke, S., Lai, C., and Miltz, J., Properties of Recycled High Density Polyethylene, *J. Appl. Polym. Sci.*, **43**, 2149 - 2150 (1991)

Ram, A., and Getz, S., Reprocessing and Shear Modification of Polyethylene, *J. Appl. Polym. Sci.*, **29**, 2508 (1984).

Rosen, S. L.,Fundamental Principles of Polymeric Materials, 2nd ed., John Wiley & Sons, New York, 249 (1993).

Sammes, N. M. and Woodward, V. G., *Materials World*, May, 248 (1994).

Schwartz, S. S. and Goodman, S. H., Plastics Materials and Processes, Van Nostrand Reinhold, New York, 103 (1982).

Sperati, C. A., Franta, W. A. and Strakwaether, H. W. JR, The Molecular Structure of Polyethylene. V. The Effect of Chain Branching and Molecular Weight on Physical Properties, *J. Am. Chem. Soc.*, **75**, 6131 (1953).

Unterreiner, R., HDPE market and product trends, *SPE ANTEC Tech.*, **3**, 3423 (1995).

Wigotsky, V., Packaging : To market to market, *Plastic Engineering*, June , **51**, 6, 16 (1995).

Zahavich, A. T. P., Latto ,B. and Vlachopoulos, J., Change in ESCR, polysipersity and crystallinity of HDPE with multiple extrusion passes, *SPE ANTEC Tech*, **2**, 2053 - 2054 (1995).

APPENDIX

The heat of fusion (H_f) can be converted to the percentage of crystalline by using the following equation ;

$$\begin{aligned} X \% &= 100 \times \Delta H_f / \Delta H_f^o \\ X \% &= \text{the percentage of crystallinity} \\ \Delta H_f &= \text{the heat of fusion from DSC thermogram} \\ \Delta H_f^o &= \text{the hypothetical heat of fusion of} \\ &\quad \text{a perfectly crystalline material} \\ &\approx 288 \text{ J/g} \end{aligned}$$

CURRICULUM VITAE

Name : Ms. Ying-anong Arthatasart
Birth date : April 4, 1973
Nationality : Thai
University education :
1990 - 1993 Bachelor of Chemistry, Faculty of Science,
Kasetsart University.