รายการอ้างอิง

ภาษาไทย

- กิตติศักดิ์ พลอยพานิชเจริญ. 2543. <u>การวิเคราะห์ระบบการวัด(MSA)</u>. กรุงเทพมหานคร: สำนักพิมพ์สมาคมส่งเสริมเทคโนโลยี(ไทย-ญี่ปุ่น).
- จเด็จ ทางเจริญ. รางวัลคุณภาพแห่งชาติ The Malcolm Baldrige National Quality Award.

 <u>Productivity World</u>. ปีที่ 6 ฉบับที่ 32 (พฤษภาคม-มิถุนายน 2544): 13-19.
- เจริญ วัชระรังษี. 2542. <u>การควบคุมคุณภาพสมัยใหม่</u>. กรุงเทพมหานคร: สำนักพิมพ์อักษร ประเสริฐ.
- ฐานกร อิงอมรรัตน์. 2540. <u>การประเมินของระบบการจัดการคุณภาพด้วยตนเองสำหรับ</u>
 <u>บริษัทโทรคมนาคมไทย</u>. วิทยานิพนธ์ปริญญามหาบัณฑิต สาขาวิชาการจัดการทาง
 วิศวกรรม จุฬาลงกรณ์มหาวิทยาลัย.
- ปารเมศ ชุติมา. 2545. <u>การออกแบบการทดลองทางวิศวกรรม</u>. กรุงเทพมหานคร: สำนัก พิมพ์แห่งจุฬาลงกรณ์มหาวิทยาลัย.
- วิเชียร เบญจวัฒนาผล และสมชัย อัครทิวา. 2545. Why-Why Analysis เทคนิคการ วิเคราะห์อย่างถึงแก่นเพื่อปรับปรุงสถานประกอบการ. กรุงเทพมหานคร: สำนักพิมพ์สมาคมส่งเสริมเทคโนโลยี(ไทย-ญี่ปุ่น).
- วีรพจน์ ลือประสิทธ์สกุล. การตรวจวินิจฉัยคุณภาพของระบบบริหารด้วยตนเองเพื่อความ เป็นเลิศในการบริหารธุรกิจ. <u>Management Best Practices</u>. ปีที่ 2 ฉบับที่ 6 (มีนาคม-เมษายน 2545): 37-43.
- สถาบันเพิ่มผลผลิตแห่งชาติ. 2545. Thailand Quality Award เกณฑ์รางวัลคุณภาพแห่ง ชาติ เพื่อองค์กรที่เป็นเลิศ. กรุงเทพมหานคร: สถาบันเพิ่มผลผลิตแห่งชาติ.
- สถาบันเพิ่มผลผลิตแห่งชาติ. 2543. <u>กรณีศึกษา Best Practices การบริหารกระบวนการ</u>

 <u>Process Management เล่มที่ 1</u>. กรุงเทพมหานคร: สถาบันเพิ่มผลผลิตแห่งชาติ.
- สถาบันเพิ่มผลผลิตแห่งชาติ. 2545. <u>กรณีศึกษา Best Practices การบริหารกระบวนการ</u>

 <u>Process Management เล่มที่ 2</u>. กรุงเทพมหานคร: สถาบันเพิ่มผลผลิตแห่งชาติ.
- สถาบันเพิ่มผลผลิตแห่งชาติ. 2545. <u>Benchmarking ทางลัดสู่ความเป็นเลิศทางธุรกิจ</u>. กรุงเทพมหานคร: สถาบันเพิ่มผลผลิตแห่งชาติ.
- สมชาติ น้อยสิริสุข. ก้าวแรกสู่รางวัลคุณภาพแห่งชาติ. <u>Productivity World</u>. ปีที่ 6 ฉบับที่ 32 (พฤษภาคม-มิถุนายน 2544): 21-28.
- สมพงษ์ เข็มทองวงศา. 2542. การปรับปรุงประสิทธิภาพการผลิตโดยการใช้การตรวจวินิจฉัย องค์กร: กรณีศึกษาอุตสาหกรรมการผลิตกระป๋อง. วิทยานิพนธ์ปริญญามหาบัณฑิต ภาควิชาวิศวกรรมอุดสาหการ จุฬาลงกรณ์มหาวิทยาลัย.

ภาษาอังกฤษ

- A.I.A.G. 1995. <u>Statistical Process Control (SPC) Reference Manual</u>. Second Edition. A.I.A.G.
- A.I.A.G. 2002. <u>Measurement Systems Analysis (MSA) Reference Manual</u>. Third Edition. A.I.A.G.
- Bendell, T., and Boulter, L. 1998. <u>Benchmarking for Competitive Advantage</u>. USA: Pitman Publishing.
- Electronic Industries Association. 1992. <u>Assessment of Quality Levels in PPM Using</u>
 Variables Test Data (EIA-591 Standard). EIA.
- Fasser, Y., and Brettner, D. 1992. <u>Process Improvement in Electronics Industry.</u>
 Chichester: John Wiley & Sons.
- Kaplan, R. S., and Norton, D. P. 1996. <u>The Balanced Scorecard</u>. USA: Harvard College.
- Lee, S. F., and Andrew, S. K. 2000. Strategy formulation framework for vocational education: integrating SWOT analysis, Balanced scorecard, QFD methodology and education criteria. Managerial Auditing Journal. 15: 407-423.
- Ogura, H. 2002. <u>Naze Naze Bunseki Tettei Katsuyo Jyutsu- "Naze ?" kara Hajimaru Shokuba no Kaizen-. Japan: JIPM.</u>
- Omachonu, V. K., and Ross, J. E. 1994. <u>Principles of Total Quality</u>. Florida: St. Lucie Press.
- Pannirselvam, P. G., and Ferguson, A. L. 2001. A study of the relationships between the Baldrige categories. <u>International Journal of Quality & Reliability</u>

 Management. 18: 14-34.
- Quirk, M., and Serda, J. 2001. <u>Semiconductor Manufacturing Technology</u>. UK: R.R. Donnelley & Sons.
- Rho, B., and Lee, S. 2000. A causal model based on the Malcolm Baldrige National

 Quality Award: An Empirical study of Korean manufacturers. International

 Journal of Operations & Production Management 20: 520-533.
- Zairi, M., and Postgrad, L. 1996. <u>Benchmarking for Best Practices</u>. USA: McGraw-Hill.

ภาคผนวก

ภาคผนวก ก.

คำจำกัดความของปัญหาที่ FVI และ FOI

Contamination lead คราบสกปรกบนขาลืด

สิ่งแปลกปลอมหรือคราบสกปรกบนขาลืด ซึ่งไม่ได้เป็นส่วนหนึ่งส่วนใดของขาลืดตาม แบบที่กำหนดมา

Chip package แพคเกจบิ่น

แพคเกจซึ่งมีบางส่วนหลุดหายไป/ไม่สมบูรณ์เนื่องมาจากการแตกหักเพราะได้รับแรง กระทบ

Incomplete mold โมลด์ใม่สมบูรณ์

แพคเกจที่มีบางส่วนขาดหายไป/ไม่เป็นไปตามรูปแบบอันเนื่องมาจากการโมลด์ไม่ สมบูรณ์

Bent lead ขาลีดงอ

ขานดที่ถูกเปลี่ยนตำแหน่ง/รูปแบบไปจากเดิม ซึ่งปกติจะทำมุม 90 องศากับด้านยาว ของแพดเกจ

Coplanarity lead ลีดต่างระดับ

ความเป็นระนาบของขาลีดเมื่อยูนิตวางอยู่บนพื้นราบ

Clamp mark กดบ่าลืด

มีแรงกระทำบนปาลีดทำให้เกิดรอยกดบนบ่าลีด

Mold flash โมลด์แฟลช

พลาสติกส่วนเกินด้านหัวหรือท้ายของแพคเกจหรือระหว่างขาลึดหรืออยู่บนผิวลึดเมื่อ วัดจากขอบของแพคเกจ

Scratch on package รอยขีดข่วนบนแพคเกจ

รอยขีดข่วนที่เกิดจากแรงกระทบซึ่งทำให้ผิวของแพคเกจไม่เรียบ

Fade mark เฟดมาร์ก

สิ่งแปลกปลอมหรือคราบสกปรกที่ฝังตัวอยู่ในร่องมาร์ค

Excessive solder ตะกั่วส่วนเกิน

ส่วนของตะกั่วที่ยื่นออกมาทำให้ขาลีดมีความกว้าง ความยาวหรือความหนาเพิ่มขึ้นเมื่อ เทียบกับขาลีดขาอื่นในแพคเกจเดียวกัน

Mixed mark มาร์คปนกัน

ล็อตที่มีผลิตภัณฑ์ที่แพคเกจ/ลีดเหมือนกัน แต่มียูนิตบางส่วนที่มีมาร์คไม่ตรงกับ เอกสารการผลิต (PT)

Reverse unit ยูนิตกลับหัว

ยูนิตกลับหัวและหงายท้องในภาชนะบรรจุ โดยสลับด้าน Top mark และ Back mark

Non plate ลีดแดง

ผิวลึดบริเวณที่ทำการชุปไม่ติด ซึ่งสามารถเห็นเนื้อโลหะของลึดเฟรม

Misorientation ยูนิตกลับหัว 180 องศา

ยูนิตที่มีทิศทางการวางตัวแตกต่างจากยูนิตอื่นในภาชนะบรรจุ โดยเทียบกับทิศทางของ มาร์คหรือทิศทางของพินวันของยูนิตอื่นที่วางตัวถูกต้อง หรืออาจเทียบกับทิศทางของ ภาชนะบรรจุ

Broken wire ลวดขาด

ลวดที่เชื่อมระหว่าง Die และ Lead ขาดและทำให้เชื่อมไม่ครบวงจร

Wrong packing label ลาเบลการบรรจุหีบห่อผิด

ลาเบลการบรรจุหีบห่อไม่ตรงกับรายละเอียดที่ลูกค้ากำหนดไว้ในเอกสาร การผลิต PT

ภาคผนวก ข.

คำจำกัดความที่ใช้ในงานวิจัย

Lead ล็ด

ขาโลหะของผลิตภัณฑ์ เป็นโลหะที่อยู่รอบๆ DAP

Package แพคเกจ

ส่วนลำตัวของผลิตภัณฑ์

Die Attach Pad (DAP)

เป็นโลหะสี่เหลี่ยมที่อยู่ตรงกลางของแผ่นเฟรมเพื่อรองรับได

Ball

ลวดที่เชื่อมกับแพดบนได

Weld

ลวดที่เชื่อมกับลีดเฟรม

Pin one พินวัน

ขาลืดขาที่หนึ่งของผลิตภัณฑ์ซึ่งใช้บอกทิศทางของแพคเกจ

Mils มิลส์

มิลลิอินซ์

Process Traveller (PT)

เอกสารแสดงสถานะการผลิต

Process Engineer (PE)

วิศวกรการผลิต

Equipment Engineer (EE)

วิศวกรเครื่องจักร

Quality Engineer (QE) วิศวกรคุณภาพ

ภาคผนวก ค.

ผลการวิเคราะห์ทางด้านสถิติโดยใช้ โปรแกรมสำเร็จรูป SPSS สำหรับการผลักบอล

Descriptives

Descriptive Statistics

	N	Minimum	Maximum	Mean	Std. Deviation
power	360	65.00	75.00	70.0000	4.0882
force	360	40.00	45.00	42.5000	2.5035
bst	360	49.60	89.50	70.4969	11.0832
Valid N (listwise)	360				

Univariate Analysis of Variance

Between-Subjects Factors

		N
power	65.00	120
	70.00	120
	75.00	120
force	40.00	180
	45.00	180

Tests of Between-Subjects Effects

Dependent Variable: bst

Dependent variable.					
Source	Type III Sum of Squares	df	Mean Square	F	Sig.
Corrected Model	24801.788 ^a	5	4960.358	90.999	.000
Intercept	1789134.903	1	1789134.903	32822.109	,000
POWER_	22107.922	2	11053.961	202.788	.000
FORCE	1529.757	1	1529.757	28.064	.000
POWER_ * FORCE	1164.110	2	582.055	10.678	.000
Error	19296.559	354	54.510		
Total	1833233.250	360			
Corrected Total	44098.347	359			

a...R Squared = .562 (Adjusted R Squared = .556)

Post Hoc Tests

power

Multiple Comparisons


Dependent Variable: bst


LSD


		Mean		-	95% Confidence Interval		
(I) power	(J) power	Difference (니니)	Std. Error	Sig.	Lower Bound	Upper Bound	
65.00	70.00	-13.5633*	.9532	.000	-15.4379	-11.6888	
	75.00	-18.5450*	.9532	.000	-20.4196	-16.6704	
70.00	65.00	13.5633*	.9532	.000	11.6888	15.4379	
	75.00	- 4.9817*	.9532	.000	-6.8562	-3,1071	
75.00	65.00	18.5450*	.9532	.000	16.6704	20.4196	
	70.00	4.9817*	.9532	.000	3.1071	6.8562	

Based on observed means.

Profile Plots








^{*} The mean difference is significant at the .05 level.


Interactive Graph



Error Bars show Mean +/- 3.0 SD




Interactive Graph



Error Bars show Mean +/- 3.0 SD

Distribution



ภาคผนวก ง.

แผนการแก้ไขเมื่อออกนอกการควบคุมสำหรับการผลักบอล

Out of control corrective action plan

c	peration :	Lea	d bo	nd	Cha	racter	istic :	Ва	li sh	ear	stre	ngth	1											M/C no. :	
_				0.0	Opera	-1		ib I a														T		:E1-	
\vdash			г—	<u>u.c.,</u>	Opera	ator re	Spons	T		O•	of o		ditio	_		<u> </u>		Г		т	Cta	iecnnicia itus	an respons	ible	
								\vdash			_		_	_		_	ł			⊢	518	lus l			
ı					Limit			1	L	_	Xbai	r		Zon	e	s	8	e e	ي ا	1		i			
	Date	Time	Shift	ğ	וטו	+/- 1 Sigma	ХЪвг	Spec	Control	2 IN 3	4 N 5	7 Above/Below	7 Inc./Dec.	m	TOT	ಭ	Cause code	Action code	Part code		Old New		E/N	Remark	
L										\sqcup			L									İ			
										\sqcap	┪					Г	Г	Г	Г						
\vdash			-		\vdash	\vdash		\vdash	Н	\dashv	\dashv		\vdash	Н	_	Н	\vdash	H	H	\vdash		 			
-			⊢	 	\vdash	-	-	-	Н	\dashv	+		-			-	⊢	⊢	⊢	\vdash			-		
			<u> </u>	ļ				┖	Ц	Ц	\dashv		L	Ц			L	L	L	L					
								Γ			\top		Г	П		Γ	Γ	Γ	Γ						
			\vdash					\vdash	Н	\dashv	\top		\vdash	П		Т	Т	T	T					-	
늗		L			l	1		<u> </u>	<u>ш</u>	_			<u>-</u>	Щ	_	_		_	_	<u></u>	-			<u> </u>	_
-	de/Cause Heater blo	cr temp	out	of sne				-	de//		on						_	de/		_	ct force		! K Stand	hy nower	
	Poor condi								Cal		te										at powe		L Good	tand by power ood die	
	Bonding pa		r					1	Ch	-	е						C 1st Contact time				M Top plate				
	Die problei								Cle		_						D 1st Force				N Windo				
	Poor clamp EFO box	oing sei	ир					1	De								E 1st Power F Capilary				O BQM I				
	Wire clam	p gap						1	Inc								1 ' '				1	clamp gap			
	BQM boar	d									-off	with	1				H Heater block F				R Modul				
	DSP								Tur		o	- 141 -									S Good				
	Shear test		tails	1				14	Utr	ier (Spe	CITIC	aeı	ans)			RUS	se v	me			2 Other	(Specific details)	
											41.							_							_
\vdash			C A	USE	estri	cted	corr	eci	ive	ac	tio	n te	or e	eac	n p	os						t be fol	lowed.		
_	Heater blo	ck temp			c			В	-H	Cal	ibrat	te ho	eate	r ble	ock		_		N.N.	EC	IIVE /	ACTION.	-		
				·				G	-H	Inci	reas	e he	eate	r blo	ck										
L								-	$\overline{}$	_	rea			er b	ock										
В	Poor cond	tion / se	et up	of cap	pilary						an c														
										_	n ca ange			~											
c	Bonding pa	aram ete	er					+-	$\overline{}$	_	ibrat					_			_		G-A	Increase	1st contact	t force	
1								F			crea				act f	orce	•				G-B		1st contact		
1											crea						er				1	4	1st contact	t tim e	
											rea					m e					1	Increase			
								1			rea										1	Increase	1st power		
										Decrease rise time Decrease stand by power										1	stand by p	ower			
	1										crea					_				_	L :				
D	Die proble							-	$\overline{}$		nfirm			lie		_	_							<u> </u>	
E	Poor clam	ping set	пр						- 1	_	n cl			- m	100						C-M C-N	Change t		m n	
F	EFO box							-	_		ange ibra1					_		_		_	C-N	Change v	window clar	mp	
G	Wire clam	p gap						-	_		reas					ıp									_
Н	BQM boar							1.	0	Tur	ne B	QM	boa	ırd											
1	DSP										buy-				od fr	ame	В								
1	Shear test	er									ange ibrat														
—	<u> </u>							+ ⁴	-1	U a	ural	ic ill	uuu												

ภาคผนวก จ. การศึกษา GR&R สำหรับเครื่องทดสอบการผลักบอล

GAGE REPEATABILITY AND REPRODUCIBILITY ANALYSIS

Gage: Ball shear tester ID No.: 1736 Model: Dage

Part: Integrated circuit Spec: 25 Grams Min. Tolerance 10 Grams

Name		A : Chon	проо R.			B: S	unit M.			C : Po	rntip P.		Parts Ave.
Sample	1' st Trail	2' nd Trail	3' rd Trail	Range	1' st Trail	2' nd Trail	3' rd Trail	Range	1' st Trail	2' nd Trail	3' rd Trail	Range	Χ _P
1	25.03	25.02	24.99	0.04	25.01	25.02	25.03	0.02	24.99	24.98	24.98	0.01	25.006
2	30.04	30.04	30.02	0.02	29.99	30.02	29.98	0.04	30.04	30.03	30.02	0.02	30.020
3	35.04	35.04	35.04	0.00	35.04	35.03	35.02	0.02	35.02	35.03	35.05	0.03	35.034
4	40.07	40.05	40.04	0.03	40.05	40.05	40.06	0.01	40.06	40.06	40.06	0.00	40.056
5	50.01	50.01	50.01	0.00	50.05	50.06	50.06	0.01	49.98	50.00	50.02	0.04	50.022
6	55.06	55.06	55.08	0.02	55.09	55.08	55.07	0.02	55.06	55.05	55.04	0.02	55.066
7	60.09	60.12	60.09	0.03	60.10	60.10	60.11	0.01	60.11	60.11	60.10	0.01	60.103
8	75.15	75.16	75.17	0.02	75.14	75.14	75.14	0.00	75.16	75.14	75.14	0.02	75.149
9	100.17	100.16	100.16	0.01	100.18	100.19	100.18	0.01	100.19	100.19	100.17	0.02	100.177
10	125.10	125.11	125.15	0.05	125.11	125.14	125.13	0.03	125.13	125.13	125.18	0.05	125.131
Total	595.76	595.77	595.75	0.22	595.76	595.83	595.78	0.17	595.74	595.72	595.76	0.22	RP
	XA	59.576	R _A	0.022	Z _B	59.579	R _B	0.017	\overline{X}_{c}	59.574	R _c	0.022	100.126

R _A	Ŕ _B	R _c	Sum	R
0.0220	0.0170	0.0220	0.0610	0.0203

Trial	2	3
D4	3.27	2.68

Max X	Min X	X Diff
59.579	59.574	0.005

UCL_s = R * D4 0.054493333

Measument Unit Analyze

Repeatability * Equipment Variation (E.V)

E.V.	= R * K1	0.0620

Trial 2 3

K1 4.56 3.05

% Tolerance Analysis

% E.V. = 100 * (E.V.) / (Tolerance) 0.6202

Repeatability * Appraiser Variation (A.V.)

A.V. =
$$(Abs[(X_{diff})*(K2)]^2 - Abs[(E.V.)^2/(n*r)])^{1/2}$$

0.0074

 Operator
 2
 3

 K2
 3.65
 2.7

% A.V. = 100 * (A.V.) / (Tolerance) 0.0735

n = Number of Parts = 10

r = Number of Trial = 3

Repeatability and Reproducibility (R&R)

R & R =
$$(Abs[(E.V.)^2 + (A.V.)^2])^{1/2}$$

0.0625

Part Variation (P.V.)

P.V. = (R_P * K3) 162.2034

Part	2	3	4	5	6	7	8	9	10
КЗ	3.65	2.7	2.3	2.08	1.93	1.82	1.74	1.67	1.62

Total Variation (T.V.)

T.V. =
$$(Abs[(R&R)^2 + (P.V)^2])^{1/2}$$

162.2034

ภาคผนวก ฉ.

การทดสอบทางสถิติ โดยใช้โปรแกรมวิเคราะห์ทางสถิติสำเร็จรูป SPSS สำหรับการหาวัสดุรองรับพื้นโต๊ะที่วางเครื่องทดสอบการผลักบอลมิให้มีการสั่นสะเทือน

ผลการวิเคราะห์มีดังต่อไปนี้

Descriptive Statistics

	N	Minimum	Maximum	Mean	Std. Deviation
before	50	40.80	49.70	44.7480	2.1035
after	50	66.40	69.80	67.9940	.9110
Valid N (listwise)	50				

การทดสอบ T-Test

Paired Samples Statistics

		Mean	N	Std. Deviation	Std. Error Mean
Pair 1	before	44.7480	50	2.1035	.2975
	after	67.9940	50	.9110	.1288

Paired Samples Test

		-	Paire	ed Difference	s		·		
					95% Coi	nfidence			
				Std. Error	Interval of th	e Difference			
		Mean	Std. Deviation	Mean	Lower	Upper	t	df	Sig. (2-tailed)
Pair 1	before - after	-23.2460	2.2413	.3170	-23.8830	-22.6090	-73.339	49	.000

ภาคผนวก ช.

การประเมินตนเองโดยอาศัยโครงสร้างรางวัลคุณภาพแห่งชาติก่อนการปรับปรุง

(แนวทางนำมาจากแบบประเมินตนเองของคุณสังวร รัตนรักษ์ สถาบันเพิ่มผลผลิตแห่งชาติ)

	Item	Details	Score								
	HeIII	Details	0	10-20%	30-40%	50-60%	70-80%	90-100%			
	6.1 Produ	ıct and Service Processes									
	6.1.1	Identify your design processes for products**/services and their ralated				A1/A					
ent		production/delivery systems and processes.	N/A								
Management	6.1.2	Incorporate changing requirements into product** and process designs.				N/A					
lana	6.1.3	Incorporate new technology, i.e. e-tech, into products/processes.									
1	6.1.4	Ensure design processes address design quality and cycle time, transfer									
Process		of learning, cost control, technology, and other efficiency/effectiveness				0					
6. P		factors.									
	6.1.5	Design your key processes to meet all key operational performance									
	170	requirements.									
	6.1.6	Coordinate and test design/production/delivery processes and how your						_			
		ensure trouble-free and timely introduction of products and services.									

Item	Details			5	Score		
Item	Details	0	10-20%	30-40%	50-60%	70-80%	90-100%
6.1.7	Identify key performance requirements for your key production/delivery processes.					si.	
6.1.8	Ensure day-to-day operations meet the requirements.						
6.1.9	Monitor key performance measures for control/improvement of key						
	processes including in-process, customer, supplier/partner inputs.						
6.1.10	Perform inspections, tests, audits to minimize warranty costs.						
6.1.11	Improve your key processes to achieve better performance and how						
	improvements are shared with others.						
6.2 Busin	ess Processes		•				
6.2.1	Determine what your key business processes are for business growth and success.						
6.2.2	Determine key requirements using customers, suppliers, partners as appropriate of the above.					2000	
6.2.3	Design and perform these processes to meet the requirements of the above.						
6.2.4	Determine key measurements for the control and improvement of the above including in-process measures, customer and supplier inputs.						

The Tape

	Item	Datails			S	Score		
	nem	Datails		10-20%	30-40%	50-60%	70-80%	90-100%
	6.2.5	Minimize costs associated with process/performance audits, inspections, and tests.						
	6.2.6	Improve your business processes to achieve better performance and keep them current with business needs.				7.35		
nt.)	6.3 Suppo	ort Processes					. 4	
ent (Co	6.3.1	Determine what your key business processes are for supporting daily operations and employees in delivering your products/services.						
Process Management (Cont.)	6.3.2	Determine key requirements using internal customers as appropriate of the above.						
rocess N	6.3.3	Design and perform these processes to meet the requirements of the above.						
6. Р	6.3.4	Ensure day-to-day operations of above processes meet key performance requirements.						
	6.3.5	Determine key measurements for the control and improvement of the above including in-process measures and internal customer inputs.					***	
	6.3.6	Minimize costs associated with process/performance audits, inspections, and tests.						

£	Item	Details			S	Score		
ss (Con	Item	Details	0	10-20%	30-40%	50-60%	70-80%	90-100%
6. Process Management (Cont.)	6.3.7	Improve your support processes to achieve better performance and keep them current with business needs.						
	7.4 Organ	izational Effectiveness			1			L
	7.4.1	Customers quality complaints (CQC)						
छ	7.4.2	Defects part per million (DPPM)						
Results	7.4.3	Process capability index (C _{pk})						
	7.4.4	Cycle time						7
Business	7.4.5	Processes yield						
	7.4.6	Time to market						
7.	7.4.7	Use of technology				and the state of t		
	7.4.8	Supply chain costs						
	7.4.9	Environmental and regulatory complaints						

Remarks: ** This thesis does not cover the "Products Design"

ภาคผนวก ซ.

การประเมินตนเองโดยอาศัยโครงสร้างรางวัลคุณภาพแห่งชาติหลังการปรับปรุง

(แนวทางนำมาจากแบบประเมินตนเองของคุณสังวร รัตนรักษ์ สถาบันเพิ่มผลผลิตแห่งชาติ)

	Item	Details			S	Score				
	Item	nem Belans		10-20%	30-40%	50-60%	70-80%	90-100%		
	6.1 Produ	uct and Service Processes								
	6.1.1	Identify your design processes for products**/services and their ralated				N/A				
ent		production/delivery systems and processes.				IN/A				
agement	6.1.2	Incorporate changing requirements into product** and pro_ess designs.	N/A							
Mana	6.1.3	Incorporate new technology, i.e. e-tech, into products/processes.						1		
SS	6.1.4	Ensure design processes address design quality and cycle time, transfer								
Proce		of learning, cost control, technology, and other efficiency/effectiveness								
6. P		factors.								
	6.1.5	Design your key processes to meet all key operational performance								
		requirements.								
	6.1.6	Coordinate and test design/production/delivery processes and how your								
		ensure trouble-free and timely introduction of products and services.								

	Item	em Details			S	Score				
	nem	Details	0	10-20%	30-40%	50-60%	70-80%	90-100%		
	6.1.7	Identify key performance requirements for your key production/delivery processes.								
	6.1.8	Ensure day-to-day operations meet the requirements.								
	6.1.9	Monitor key performance measures for control/improvement of key								
		processes including in-process, customer, supplier/partner inputs.								
ent	6.1.10	Perform inspections, tests, audits to minimize warranty costs.								
gem	6.1.11	Improve your key processes to achieve better performance and how								
lana		improvements are shared with others.								
SS N	6.2 Business Processes									
6. Process Management	6.2.1	Determine what your key business processes are for business growth and success.								
	6.2.2	Determine key requirements using customers, suppliers, partners as appropriate of the above.								
	6.2.3	Design and perform these processes to meet the requirements of the above.								
	6.2.4	Determine key measurements for the control and improvement of the above including in-process measures, customer and supplier inputs.								

Item	Datails			S	core		
nem	Datalis	0	10-20%	30-40%	50-60%	70-80%	90-100%
6.2.5	Minimize costs associated with process/performance audits, inspections,						
	and tests.						
6.2.6	Improve your business processes to achieve better performance and						
	keep them current with business needs.				- 6		
6.3 Supp	ort Processes						
6.3.1	Determine what your key business processes are for supporting daily						
	operations and employees in delivering your products/services.						
6.3.2	Determine key requirements using internal custome, as appropriate of						
	the above.						
6.3.3	Design and perform these processes to meet the requirements of the						
	above.						
6.3.4	Ensure day-to-day operations of above processes meet key performance						
	requirements.						
6.3.5	Determine key measurements for the control and improvement of the						
	above including in-process measures and internal customer inputs.						
6.3.6	Minimize costs associated with process/performance audits, inspections,						
	and tests.						
						1	

in we

3	Itom	Item Details			S	Score		
ss (Cont	item			10-20%	30-40%	50-60%	70-80%	90-100%
6. Process Management (Cont.)	6.3.7	Improve your support processes to achieve better performance and keep them current with business needs.						
	7.4 Organ	izational Effectiveness						
	7.4.1	Customers quality complaints (CQC)						
્ ક	7.4.2	Defects part per million (DPPM)						
Results	7.4.3	Process capability index (C _{pk})				161		
	7.4.4	Cycle time						
Business	7.4.5	Processes yield						
	7.4.6	Time to market						
7.	7.4.7	Use of technology						
	7.4.8	Supply chain costs						
	7.4.9	Environmental and regulatory complaints						

Remarks: ** This thesis does not cover the "Products Design"

ภาคผนวก ฌ.

เกณฑ์การประเมินตนเองโดยอาศัยโครงสร้างรางวัลคุณภาพแห่งชาติ

(แนวทางนำมาจากแบบประเมินตนเองของคุณสังวร รัตนรักษ์ สถาบันเพิ่มผลผลิตแห่งชาติ)

ARTCULATED SCORING GUIDELINES FOR APPROACH/DEPLOYMENT ITEMS (CATEGORIES 1-6)

SCORING	SYSEMATIC	DEPLOYMENT	CONTINUOUS
RANGE	APPROACH (SA)	(DE)	IMPROVEMENT (CI)
0%	Anecdotal; no system	Anecdotal; no evidence Of deployment.	Anecdotal; no evidence of continuous Improvement.
10-20%	There are pockets of organizational practices that are responsive to about 20-25% of the sub-areas or numbered requirements of the Item; however, these practices lack an overall system architecture or a process map.	The organizational practices in response to the Item are implemented in 10-30% of all applicable areas or work units covered in the Item.	 Although the organization is beginning to recognize problems pertaining to this Item, it is still generally reactive.

30-40%	•	There are organizational practices that address	•	The organizational practices in	•	Actions have been
		about <u>25-50%</u> of the Item's sub-areas.		response to the Item are		implemented to improve the
	•	There is an <u>evolving</u> system architecture or		implemented in 40-60% of all		process(es) covered in the
6		process map that encompasses the above		applicable areas or work units		Item. However, these
		organizational practices. Because these		covered in the Item.		improvements do not appear to
		processes are relatively well established, they	•	Among the areas/units where the		be the results of a continuous
	;	are capable of being demonstrated "on the		practices are implemented, about		improvement mechanism (e.g.,
	1	factory floor" or on the organization's intranet.		20-25% are in the most advanced		Plan-Do-Check-Act or Plan-Do-
				stages of implementation.		Study-Act cycle).
50-60%	•	There are organizational practices that respond	•	The organizational practices in	•	The organization has a
	1	to all of the Item's Areas to Address and about		response to the Item are		PDCA/PDSA cycle in place for
	1	50-70% of the Item's sub-areas, and these are		implemented in 70-90% of all		the process(es) covered in the
	1	reflected in an overall system architecture or		applicable areas or work units		Item.
		process map.		covered in the Item.	•	The process has undergone at
	•	The organization's response to the Item is	•	Among the areas/units where the		least 1-2 cycles of refinement
		aligned with all other Criteria Categories related		practices are implemented, about		or fact-based improvement.
	1	to the Item and at least one-third of the other		25-50% are in the most advanced		
		<u>Criteria Items</u> related to the Item.		stag as of implementation.		

70-80%

- There are organizational practices that respond to all of the Item's Areas to Address and about 75-100% of the Item's sub-areas, and these are reflected in an overall system architecture or process map.
- The organization's response to the Item is aligned with at lease <u>two-thirds</u> of the other Criteria Items related to the Item.
- The organizational practices in response to the Item are implemented in 70-90% of all applicable areas or work units covered in the Item.
- Deployment is complete in at least
 75% of all major functions and in
 more than 50% of support functions.
- Among the areas/units where the practices are implemented, about 50-75% are in the most advanced stages of implementation.

- The process has undergone at least 3-5 cycles of refinement or fact-based improvement.
- The organization applies a PDCA/PDSA to the improvement process itself.
- The process has already achieved <u>best practice</u> status, as a result of continual improvement and lessons learned.
- In the organization practices

 knowledge management by implementing a system for organization-wide sharing of key skills and systems and dissemination of best demonstrated practices related to this Item.

90-100%

- There are organizational practices that respond to all of the Item's Areas to Address and about 75-100% of the Item's sub-areas, and these are reflected in an overall system architecture or process map.
- The organization's response to the Item is aligned with <u>all</u> of the other Criteria Items related to the Item.
- The organizational practices in response to the Item are implemented in <u>all</u> applicable areas or work units covered in the Item, with about <u>75-100%</u> in the most advanced stages of implementation.
- The organization's
 PDCA/PDSA cycle in place for
 the process(es) covered in the
 Item and the organization's
 knowledge management
 practices are recognized as
 <u>benchmarks</u> among
 comparable organizations.

ARTCULATED SCORING GUIDELINES FOR RESULTS ITEMS (CATEGORY 7)

SCORING	KAY AREAS AND	TRENDS	COMPARISONS AND
RANGE	LEVELS (KALE)	(TR)	BENCHMARKS (CO)
0%	 No results are reported for the performance measures relevant to the Item. If results are reported, all results do not meet the organization's goals for those measures. 	No trends are reported.	No comparisons are reported.
10-20%	 Results are reported for at least one-third of the Item-related measures reported in the organization's performance scorecard (Item 1.1b), strategy (2.1b), and action plans (2.2b). At least 10-30% of Item-related measures reported in the organization's performance scorecard, strategy, and action plans meet 	 At least 10-30% of Item-related measures reported in the organization's performance scorecard (Item 1.1b), strategy (2.1b), and action plans (2.2b) have positive improvement trends (with 2-3 data points). 	 No comparisons are reported, although the organization collects comparative data and information [per information reported in Items 2.2b(2), 3.2b (3), and 4.1a(1)].

	the goals of the organization for those		
	measures.		
30-40%	Results are reported for at least two-thirds of	At least 40-60% of Item-related	At least 10-30% of Item-related
	the Item-related measures reported in the	measures reported in the	measures reported in the
	organization's performance scorecard (Item	organization's performance	organization's performance
	1.1b), strategy (2.1b), and action plans	scorecard (Item 1.1b), strategy	scorecard (Item 1.1b), strategy
	(2.2b).	(2.1b), and action plans (2.2b) have	(2.1b), and action plans (2.2b)
	At least 40-60% of Item-related measures	positive improvement trends. Some	have comparative results.
	reported in the organization's performance	trends may be sustained.	The above results meet or
	scorecard, strategy, and action plans meet		exceed industry average or the
1.3	the organization's goals for those measures.		average for comparable
			organizations. Some results
			may even approach those of
			largest competitor, industry
			best, or benchmark levels.
50-60%	Results are reported for all Item-related	At lease <u>70-90%</u> of Item-related	At least 40-60% of Item-related
	measures reported in the organization's	measures reported in the	measures reported in the
	performance scorecard (Item 1.1b), strategy	organization's performance	organization's performance
	(2.1b), and action plans (2.2b).	scorecard (Item 1.1b), strategy	scorecard (Item 1.1b), strategy

	At least 70-90% of Item-related measures	(2.1b), and action plan (2.2b) have	(2.1b), and action plans (2.2b)
	reported in the organization's performance	positive improvement trends.	have comparative results that
	scorecard, strategy, and action plans meet	About <u>one-third</u> of the above	meet or exceed industry
	the goals of the organization for those	measures have positive	average or the average for
	measures.	improvement trends that are	comparable organizations.
	Results are reported for <u>at least 50%</u> of all	sustained (i.e., progressively	About <u>one-third</u> of the above
	Item-related measures reported in the other	improving).	measures that results that
	Approach/ Deployment Items related to the		meet or exceed those of
	Item. [Hereafter, these are referred to as		largest competitors, industry
	"second-level measures"]		best, or at benchmark levels.
	At least 40-60% of second-level measures		
	meet the organization's goals for those		
	measures.		
70-80%	Results are reported for <u>all</u> Item-related	At least <u>70-90%</u> of Item-related	• At least <u>70-90%</u> of Item-related
	measures reported in the organization's	measures reported in the	measures reported in the
	performance scorecard (Item 1.1b), strategy	organization's performance	organization's performance
	(2.1b), and action plans (2.2b), and they <u>all</u>	scorecard (Item 1.1b), strategy	scorecard (Item 1.1b), strategy
	meet organizational goals for those	(2.1b), and action plans (2.2b) have	(2.1b), and action plans (2.2b)
	measures.	positive improvement trends.	have comparative results that

property and the second
	 Results are reported for at least 75% of all second-level measures. At least 70-90% of second-level measures meet the organization's goals for these measures. In about half of the above favorable levels, the organization met its goals for the past 2-5 years. 	 About two-thirds of the above measures have positive improvement trends that are sustained (i.e., progressively improving). Although there may still be a few flat or declining trends, there are clear relationships between improvement initiatives and performance results. 	exceed industry average or the average for comparable organizations. About two-thirds of the above measures have results that meet or exceed industry best or at benchmark levels.
90-100%	 Results are reported for all Item-related measures reported in the organization's performance scorecard (Item 1.1b), strategy (2.1b) and action plans (2.2b), and all second-level measures. In at least 70-90% of all measures presented, the organization met its goals for the past 2-5 years. 	 Almost <u>all</u> of Item-related measures reported in the organization's performance scorecard (Item 1.1b), strategy (2.1b), and action plans (2.2b) have positive improvement trends. Almost <u>all</u> of the above measures have positive improvement trends that are sustained (i.e., 	Almost <u>all</u> of Item-related measures reported in the organization's performance scorecard (Item 1.1b), strategy (2.1b), and action plans (2.2b) have comparative results that exceed industry average or the average for comparable organizations.

	progressively improving).	•	Almost <u>all</u> of the above
			measures have results that
			meet or exceed industry best
			or at benchmark levels.

ประวัติผู้เขียนวิทยานิพนธ์

นางสาวสิริมา อินทวงศ์ เกิดเมื่อวันที่ 9 พฤศจิกายน พ.ศ. 2516 จังหวัดสุราษฎร์ธานี สำเร็จการศึกษาปริญญาตรีวิทยาศาสตรบัณฑิต สาขาวิชาสถิติประยุกต์ คณะวิทยาศาสตร์และ เทคโนโลยีจากมหาวิทยาลัยธรรมศาสตร์ ปี พ.ศ. 2538 และทำงานที่บริษัทเอ็นเอส อิเล็กทรอนิกส์ กรุงเทพ (1993) จำกัด ตั้งแต่ปี พ.ศ. 2538 จนถึงปัจจุบัน เข้าศึกษาต่อในระดับ ปริญญาโท สาขาวิชาวิศวกรรมอุตสาหการ คณะวิศวกรรมศาสตร์ จุฬาลงกรณ์มหาวิทยาลัย ใน ปีการศึกษา 2544

